

222 Cavalcade Street, 77009-3213
P.O. Box 8768, Houston, Texas 77249-8768
Tel: (713) 692-9151 Fax: (713) 696-6205

Attention: Grady Smith

SCAFFOLDMART

234 Dudley Street

Greenville, NC 27858

P: (252) 756-3862 / F: 252/756-3849

W/O. No.: SCA021-04-14-54902-5

P.O. No.: 6000A

Report Date: 6/1/2009


ULTIMATE LOAD TEST
5' x 5' Single Tier Scaffold Frame
Test Method: ANSI/SSFI SC100-5/05

Sample	Maximum Load (lbs)	Load (lbs) Per Leg	Load (lbs) Per Leg at 4:1 Safety Factor
5' x 5'	72,980	18,245	4,560

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products. Material submitted to our metals department will be discarded after a period of 30 days unless otherwise directed.

Stork SWL, is an operating unit of Stork Materials Technology B.V., Amsterdam, The Netherlands, which is a member of the Stork group

Respectfully Submitted


Terry Wilt
Manager, Product Evaluation