

222 Cavalcade Street, 77009-3213  
P.O. Box 8768, Houston, Texas 77249-8768  
Tel: (713) 692-9151 Fax: (713) 696-6205

Attention: Grady Smith  
**SCAFFOLDMART**  
234 Dudley Street  
Greenville, NC 27858  
P: (252) 756-3862 / F: 252/756-3849

W/O. No.: SCA021-04-14-54902-1  
P.O. No.: 6000A  
Report Date: 4/29/2009

**ULTIMATE LOAD TEST**  
**Clip-On Type Scaffold Side Bracket**  
**Test Method: ANSI/SSFI SC100-5/05**

Sample	Bracket Tube OD	Bracket Horizontal Length	Bracket Vertical Length	Max Load (lbs)	Load (lbs) at 4:1 Safety Factor
Clip-On	1.688"	20 1/4"	23"	2,795	700



Clip-On Bracket Pre-Load




Clip-On Bracket Deflection at 2,795 lbs.

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products. Material submitted to our metals department will be discarded after a period of 30 days unless otherwise directed.

Stork SWL, is an operating unit of Stork Materials Technology B.V., Amsterdam, The Netherlands, which is a member of the Stork group

Respectfully Submitted

  
Terry Wilt  
Manager, Product Evaluation